# Marking Scheme Strictly Confidential (For Internal and Restricted use only) Senior School Certificate Examination, 2023

SUBJECT: PHYSICS (042) (PAPER CODE 55/1/1)

# **General Instructions: -**

2	You are aware that evaluation is the most important process in the actual and correct assessment of the candidates. A small mistake in evaluation may lead to serious problems which may affect the future of the candidates, education system and teaching profession. To avoid mistakes, it is requested that before starting evaluation, you must read and understand the spot evaluation guidelines carefully.  "Evaluation policy is a confidential policy as it is related to the confidentiality of the examinations conducted, Evaluation done and several other aspects. Its' leakage to public in any manner could lead to derailment of the examination system and affect the life and future of
	millions of candidates. Sharing this policy/document to anyone, publishing in any magazine and printing in News Paper/Website etc may invite action under various rules of the Board and IPC."
3	Evaluation is to be done as per instructions provided in the Marking Scheme. It should not be done according to one's own interpretation or any other consideration. Marking Scheme should be strictly adhered to and religiously followed. However, while evaluating, answers which are based on latest information or knowledge and/or are innovative, they may be assessed for their correctness otherwise and due marks be awarded to them. In class-X, while evaluating two competency-based questions, please try to understand given answer and even if reply is not from marking scheme but correct competency is enumerated by the candidate, due marks should be awarded.
4	The Marking scheme carries only suggested value points for the answers
	These are in the nature of Guidelines only and do not constitute the complete answer. The students can have their own expression and if the expression is correct, the due marks should be awarded accordingly.
5	The Head-Examiner must go through the first five answer books evaluated by each evaluator on the first day, to ensure that evaluation has been carried out as per the instructions given in the Marking Scheme. If there is any variation, the same should be zero after delibration and discussion. The remaining answer books meant for evaluation shall be given only after ensuring that there is no significant variation in the marking of individual evaluators.
6	Evaluators will mark( $\sqrt{\ }$ ) wherever answer is correct. For wrong answer CROSS 'X" be marked. Evaluators will not put right ( $\sqrt{\ }$ ) while evaluating which gives an impression that answer is correct and no marks are awarded. This is most common mistake which evaluators are committing.
7	If a question has parts, please award marks on the right-hand side for each part. Marks awarded for different parts of the question should then be totaled up and written in the left-hand margin and encircled. This may be followed strictly.
8	If a question does not have any parts, marks must be awarded in the left-hand margin and encircled. This may also be followed strictly.

9	If a student has attempted an extra question, answer of the question deserving more marks should be
	retained and the other answer scored out with a note "Extra Question".
10	No marks to be deducted for the cumulative effect of an error. It should be penalized only once.
11	A full scale of marks 0 - 70(example 0 to 80/70/60/50/40/30 marks as given in Question Paper) has to
	be used. Please do not hesitate to award full marks if the answer deserves it.
12	Every examiner has to necessarily do evaluation work for full working hours i.e., 8 hours every day
	and evaluate 20 answer books per day in main subjects and 25 answer books per day in other subjects
	(Details are given in Spot Guidelines). This is in view of the reduced syllabus and number of questions
	in question paper.
13	Ensure that you do not make the following common types of errors committed by the Examiner in the
	past:-
	• Leaving answer or part thereof unassessed in an answer book.
	Giving more marks for an answer than assigned to it.  Was a totaling of marks awarded an analysis.
	<ul> <li>Wrong totaling of marks awarded on an answer.</li> <li>Wrong transfer of marks from the inside pages of the answer book to the title page.</li> </ul>
	<ul> <li>Wrong question wise totaling on the title page.</li> </ul>
	<ul> <li>Wrong totaling of marks of the two columns on the title page.</li> </ul>
	Wrong grand total.
	Marks in words and figures not tallying/not same.
	Wrong transfer of marks from the answer book to online award list.
	• Answers marked as correct, but marks not awarded. (Ensure that the right tick mark is correctly and clearly indicated. It should merely be a line. Same is with the X for incorrect answer.)
	<ul> <li>Half or a part of answer marked correct and the rest as wrong, but no marks awarded.</li> </ul>
14	While evaluating the answer books if the answer is found to be totally incorrect, it should be marked
	as cross (X) and awarded zero (0)Marks.
15	Any un assessed portion, non-carrying over of marks to the title page, or totaling error detected by the
	candidate shall damage the prestige of all the personnel engaged in the evaluation work as also of the
	Board. Hence, in order to uphold the prestige of all concerned, it is again reiterated that the
	instructions be followed meticulously and judiciously.
16	The Examiners should acquaint themselves with the guidelines given in the "Guidelines for spot
	Evaluation" before starting the actual evaluation.
17	Every Examiner shall also ensure that all the answers are evaluated, marks carried over to the title
	page, correctly totaled and written in figures and words.
18	The candidates are entitled to obtain photocopy of the Answer Book on request on payment of the
10	prescribed processing fee. All Examiners/Additional Head Examiners/Head Examiners are once again
	reminded that they must ensure that evaluation is carried out strictly as per value points for each
	answer as given in the Marking Scheme.

MARKING SCHEME: PHYSICS(042)					
	Code: 55/1/1				
Q.No.	VALUE POINTS/EXPECTED ANSWERS	Marks	Total Marks		
	SECTION –A				
1.	(b) $\frac{\overrightarrow{F}}{8}$	1	1		
2.	(d)	1	1		
	Resistance T				
3.	(d) 1 Ω	1	1		
4.	(a)	1	1		
	$\overset{\mathrm{v_d}}{\overbrace{\bigwedge}}$				
5.	(a) Repelled by both the poles.	1	1		
6.	(c) 0.19 V	1	1		
7.	(c) Resistance (r)	1	1		
8.	$(c) \in_{o} \frac{d\phi_{E}}{dt}$	1	1		
9.	(a) Zero	1	1		
10.	(c) $n^2$	1	1		
11.	(d) 95 nm	1	1		
12.	(d) Independent of A	1	1		
13.	(c)	1	1		
	v $t$				
14.	(b) it becomes a p-type semiconductor	1	1		
15.	(d) 0.01 eV	1	1		
16.	(d) Assertion (A) is false and Reason (R) is also false.	1	1		
17.	(a) Both Assertion (A) and Reason (R) are true and Reason (R) is the correct explanation of Assertion (A).	1	1		
18.	(b) Both Assertion (A) and Reason (R) are true but reason (R) is the <b>not</b> correct explanation of the Assertion (A)	1	1		
	SECTION-B				

19.			
	Calculation of acceleration of alpha particle 2		
	$\vec{F} = q(\vec{v} \times \vec{B})$	1/2	
	$= q(3 \times 10^5 \hat{i} \times (0.4 \hat{i} + 0.3 \hat{j}))N$		
	$\vec{F} = q(0.9 \times 10^5 \hat{k}) N$	1/2	
	$\vec{F} = m\vec{a} = q(0.9 \times 10^5 \hat{k})N$	1/2	
	$\vec{a} = \frac{q}{m} (0.9 \times 10^5 \hat{k}) ms^{-2}$ $= 4.8 \times 10^7 \times 0.9 \times 10^5 \hat{k}  \text{ms}^{-2}$		
	= $4.32 \times 10^{12} \ \hat{k} \ \text{ms}^{-2}$ Note: Deduct ½ mark if a student does not mention the direction of acceleration.	1/2	2
20.			
	Identification1Justification1		
	Induced electric field due to changing magnetic field is easily observed.  Induced electric field due to changing magnetic field can be easily produced by various ways like rotating/moving a coil in magnetic field, changing the	1	
	shape of coil in magnetic field, bringing bar magnet near a coil etc.	1	2
21.	(a)  Ray diagram 1 Proof of Snell's law of refraction 1		
	Incident wavefront  A' $v_1$ Medium 1  P  Medium 2 $v_2 < v_1$ Refracted wavefront	1	
	AB is incident wave front, incident at an angle i. Let τ be time taken by the wave front to travel distance BC.  BC= v <sub>1</sub> τ where v <sub>1</sub> is speed of wave in medium 1.  To determine shape of refracted wave front, we draw a sphere of radius v <sub>2</sub> τ, where v <sub>2</sub> is speed of wave in medium 2.  CE represents a tangent drawn from point C on sphere, CE is the refracted wave front.		
	sin i = $\frac{BC}{AC} = \frac{v_1 \tau}{AC}$ sin r = $\frac{AE}{AC} = \frac{v_2 \tau}{AC}$	1/2	

	$\frac{\sin i}{\sin r} = \frac{\mathbf{V}_1}{\mathbf{V}_2} = \mathbf{n}_{21}$	1/2	
	<b>Note:</b> Give full credit if student derives Snell's law by taking incident wavefront in denser medium.		
	Incident wavefront  Medium 1 $v_1$ $v_2$ $v_2$ $v_3 > v_1$ Refracted wavefront		
	OR (b)		
	Reason for preferring reflecting type telescope over refracting telescope    1/2 + 1/2	1+1	2
22.	Finding the ratio of maximum and minimum intensities 2		
	$\frac{I_{\text{max}}}{I_{\text{min}}} = \frac{(\sqrt{I_1} + \sqrt{I_2})^2}{(\sqrt{I_1} - \sqrt{I_2})^2}$	1/2	
	$= \frac{I_1 + I_2 + 2\sqrt{I_1}I_2}{I_1 + I_2 - 2\sqrt{I_1}I_2}$	1/2	
	$= \frac{5I + 4I}{5I - 4I}$	1/2	
	$=\frac{9}{1}$	1/2	
	Alternatively $\frac{I_1}{I_2} = \frac{a^2}{b^2} = \frac{4I}{I} = \frac{4}{1}$		
		1/2	
	$\frac{a}{b} = \frac{2}{1}$	1/2	

	$\frac{I_{\text{max}}}{I_{\text{min}}} = \frac{(a+b)^2}{(a-b)^2}$		1/2	
	$\frac{I_{\text{max}}}{I_{\text{min}}} = \frac{(2+1)^2}{(2-1)^2} = \frac{9}{1}$		1/2	2
23.	Calculation of potential energy of Calculation of kinetic energy of Calculation	electron 1  eV $rgy = 2 \times E_4$ eV	1/2	
	Kinetic energy = - (Total Energy) = 0.85 eV	$=-E_4$	1/ <sub>2</sub> 1/ <sub>2</sub>	2
24.	Intrinsic semiconductor  1. Pure semiconductor.  2. Low conductivity at room temperature.  3. n <sub>e</sub> = n <sub>h</sub> (Any one)  Note: Give full credit if a student w  (b)  Circuit diagram for forward and room temperature.  V-I characteristic (Forward and room temperature).	Extrinsic semiconductor  Semiconductor is Doped with impurities.  High conductivity at room temperature.  n <sub>e</sub> ≠ n <sub>h</sub> vrites any other relevant correct answer.  OR  everse biased p-n junction diode  1/2 + 1/2	1+1	

	Forward Bias  Volumeter(V)  Williammeter  (mA)  Switch  Reverse Bias	1/2 + 1/2	
	Characteristics of silicon Diode	1/2 + 1/2	2
25.			
	The diffusion current due to concentration gradient at the junction forms a space charge region consisting of immobile charge carriers. Due to this an electric field is generated at the junction giving rise to drift current in a direction opposite to diffusion current.  The potential at which diffusion current becomes equal to drift current is called potential barrier.	2	2
	SECTION -C		
26.	a) Finding electric potential at the centre Finding electric field at the centre 1 b) Finding electric potential at the centre 1  (a) Electric potential due to point charge	1/2	
	$V = \frac{kq}{R}$ Value of each charge = -q, Total charge = -12q $Total \text{ potential } V = \frac{k(-12q)}{R}$ $V = \frac{-12kq}{R} = -12q$	1/2	
	$V = \frac{-12kq}{R} = \frac{-12q}{4\pi \in_0 R}$ By symmetry the resultant of all electric field vectors becomes zero. So electric field is zero.	1	

	(b) Electric potential is a scalar quantity and does not depend on placement of charges		
	Therefore $V = \frac{-12kq}{R} = \frac{-12q}{4\pi \in_0 R}$	1	3
27.	(a)		
	Difference between resistance and impedance 1 Obtaining expression for impedance 2		
	1. Resistance is the opposition offered to both alternating current and direct current while impedance is the opposition offered to alternating current only.		
	2. Resistance is independent of frequency of source while impedance depends on frequency.		
	3. Resistance is opposition offered by material of the conductor while impedance is combined opposition offered by different electrical components such as resistor, inductor or capacitor.	1	
	(Any One) (Note: Give credit of this part if a student writes any other correct answer.)		
	$v_{\rm R}$ $v_{\rm C}$	1/2	
	$V_R = i_m R$ , $V_c = i_m X_c$ , $V_L = i_m X_L$ $i_m = \text{Peak value of current in the circuit.}$ $\overrightarrow{V_L} + \overrightarrow{V_R} + \overrightarrow{V_C} = \overrightarrow{V_m}$	1/2	
	$(V_{\rm m})^2 = V_{\rm R}^2 + (V_{\rm C} - V_{\rm L})^2$ $= (i_{\rm m}R)^2 + (i_{\rm m}X_{\rm c} - i_{\rm m}X_{\rm L})^2$ $= i_{\rm m} [R^2 + (X_{\rm c} - X_{\rm L})^2]$ $\vdots \qquad V_{\rm m}$	1/2	
	$i_{m} = \frac{V_{m}}{\sqrt{R^{2} + (X_{c} - X_{L})^{2}}}$ $i_{m} = \frac{V_{m}}{Z} \text{ where } Z = \sqrt{R^{2} + (X_{c} - X_{L})^{2}} = \text{impedance}$	1/2	


OR		
(b) Finding condition for resonance 1 Factors affecting resonant frequency 1 Graph 1		
$Z = \sqrt{R^2 + (X_L - X_c)^2}$	1/2	
For maximum current, Z should be minimum therefore to minimize Z $X_L = X_C$	1/2	
Alternatively	17	
$X_L = X_C$	1/2	
$\omega L = \frac{1}{\omega C}$ $\omega_{\rm r} = \frac{1}{\sqrt{LC}}$	1/2	
Resonant Frequency depends on value of Inductance and Capacitance	1/2 + 1/2	
$\mathbf{I}$ $\mathbf{\omega}_n$ $\mathbf{\omega}_n$	1	3
Finding a) Induced emf b) Mutual inductance between solenoid and coil  2 b) Mutual inductance between solenoid and coil		
a) magnetic field produced in the solenoid near the center $B = \mu_o nI$ Flux linked with the coil wound over solenoid $\phi = NBA = N \pi r^2 B$	1/2	
$= N \pi r^2 \mu_o nI$	1/2	
Induced emf e = $\frac{-d\phi}{dt}$ = $-\pi r^2 \text{ Nn}\mu_0 \frac{dI}{dt}$ (i)	1/2	
$= - \mu_0 \pi r^2 n N I_0 \omega \cos \omega t$	1/2	

	dI	1/2	
	b) comparing Eq (i) with $e = -M \frac{dI}{dt}$		
	$M = \mu_0 \pi r^2 nN$	1/2	3
29.	Explanation of emission of electron a) variation of photocurrent with collector plate potential for different intensity 1 b) variation of photo current with intensity of incident radiation 1   According to Einstein's photoelectric equation An electron absorbs a quantum of energy 'hu' of incident radiation. If the energy of absorbed quantum exceeds the minimum energy needed by the electron to escape from the metal surface (work function $\phi_0$ ), the electron is emitted.	1	3
	$K_{max} = hv - \phi_0$ a) $I_3 > I_2 > I_1$ $I_3$ $I_2$ $I_1$ Stopping potential $V_0$ Retarding potential $V_0$	1	
	Intensity of light →	1	3

30.

a)

Energy level diagram for hydrogen atom  $1\frac{1}{2}$  Transitions corresponding to ultraviolet region, visible region and infrared region  $\frac{1}{2} + \frac{1}{2} + \frac{1}{2}$ 



1 ½

 $\frac{1}{2}$ 

 $\frac{1}{2}$ 


1/2

Note: Award  $1\frac{1}{2}$  mark for energy level diagram if the student does not show the transitions.

OR

b)

Diagram to show variation	1
Two features of diagram	$\frac{1}{2} + \frac{1}{2}$
Reason for nuclear fusion	1



(Note: Award full credit even if a student does not mark so many elements and does not mention the values of  $E_{bn}$ .)

Features of diagram (any two)

- 1. Binding energy per nucleon is practically independent of atomic number for nuclei of middle mass number  $(30 \le A \le 170)$
- 2. The curve has maximum of about 8.75 MeV for A=56 and has a value of 7.6 MeV for A=238
- 3. Binding energy per nucleon is lower for both light nuclei (A<30) and heavy nuclei (A>170)

 $\frac{1}{2} + \frac{1}{2}$ 

Two lighter nuclei fuse together to form heavier nuclei as the binding energy per nucleon of fused heavier nuclei is more than the binding energy per nucleon of the lighter nuclei. Thus the final system is more tightly bound

	than initial system.		
	Alternatively  To extend the extendition	1	
	To attain the stability	1	3
	SECTION -D		
31.	(a)		
	i) Statement of coulomb's law and vector form 1+1 ii) Explanation of Gauss's law based on coulomb's law 1iii) Force exerted by charge A on charge B 2		
	i) Force between two point charges varies inversely with the square of distance between the charges and is directly proportional to the product of magnitude of the two charges and acts along the line joining the two charges. $\overrightarrow{F_{12}} = \frac{1}{4\pi} \underbrace{\frac{q_1 q_2}{r_{12}^2}}_{r_{12}} \widehat{r_{12}}$	1	
	Alternatively		
	$\overrightarrow{F_{12}} = \frac{1}{4\pi \in_{o}} \frac{q_{1}q_{2}}{r_{12}^{3}} \overrightarrow{r_{12}}$		
	Where $\overline{r_{12}}$ is a vector from charge $q_2$ to charge $q_1$ . ii) In derivation of Gauss's law, flux is calculated using Coulomb's law and surface area. Here coulomb's law involves $\frac{1}{r^2}$ factor and surface area involves $r^2$ factor. When product is taken, the two factors cancel out and flux becomes independent of r. iii)	1	
	$a \frac{2q}{1}B$	1∕2	
	$\vec{r} = \overrightarrow{AB} = a\hat{i} + a\hat{j}$ $r =  \overrightarrow{AB}  = \sqrt{a^2 + a^2} = \sqrt{2}a$ $\vec{F} = \frac{1}{4\pi \in_o} \frac{q_1 q_2}{r^2} \hat{r}$	1/2	

$\overrightarrow{F} =$	1	$\langle \frac{q \times 2q}{\sqrt{2}} \rangle$	$\langle \frac{(a\hat{i} + a\hat{j})}{\sqrt{a}} \rangle$
	$4\pi \in _{o}$	$\langle \overline{(\sqrt{2}a)^2} \rangle$	$\sqrt{2}a$
	_	- 2 ^	$\widehat{S}$

$$\vec{F} = \frac{1}{4\pi \in {}_{o}} \times \frac{2q^{2}}{2a^{2}} \times \frac{(\hat{i} + \hat{j})}{\sqrt{2}}$$

$$\vec{F} = \frac{1}{4\pi \in {}_{o}} \times \frac{q^{2}}{\sqrt{2}a^{2}} \times (\hat{i} + \hat{j})$$

$$\vec{F} = \frac{q^2}{4\sqrt{2}\pi \in_o a^2} (\hat{i} + \hat{j})$$

 $\frac{1}{2}$ 

 $\frac{1}{2}$ 

Note: Award 1 mark if a student calculates the magnitude of force only.

$$\left| \overrightarrow{F} \right| = \frac{1}{4\pi \in_{o}} \frac{q^2}{a^2}$$

## **Alternatively**

Give full credit if a student uses component method to solve the question.


OR

i) Derivation of electric field

2 1

- ii) Effect on electric field
- iii) Finding magnitude and direction of electric field

i)



 $\frac{1}{2}$ 

$$E_{+q} = \frac{q}{4\pi \in {}_{o}} \times \frac{1}{r^2 + a^2}$$

$$E_{-q} = \frac{q}{4\pi \in \mathcal{E}_o} \times \frac{1}{r^2 + a^2}$$

The components normal to dipole axis cancel away. The components along the dipole axis add up.

Total electric field is opposite to dipole moment.

$$\overline{E} = -(E_{+q} + E_{-q}) \cos \theta \hat{p}$$


$$= \frac{-2qa}{4\pi \in_{o} (r^{2} + a^{2})^{3/2}} \hat{p}$$

 $\frac{1}{2}$ 

 $\frac{1}{2}$ 

	ı	T
$= \frac{-\overrightarrow{p}}{4\pi \in_{o} (r^{2} + a^{2})^{3/2}}$ Deduct ½ mark if the expression of electric field is not in vector form.	1/2	
ii) At far off point $r >> a$ $\vec{r} \qquad -\vec{p}$		
$\overrightarrow{E} = \frac{-p}{4\pi \in_{o} r^{3}}$		
When distance is halved.		
$\vec{E} = \frac{-p}{4\pi \in_{o} (\frac{r}{2})^{3}}$	1/2	
$4\pi \in \left(\frac{1}{2}\right)^{3}$	72	
$=\frac{-8\vec{p}}{4\pi\in_{o}r^{3}}$		
$4\pi \in_{o} r^{3}$ $\vec{E}$ becomes 8 times	1/2	
E becomes 8 times		
iii)		
$P_{net}$ $P_{1} = q \times 2Cm  \text{(along OA)}$		
$p_1 = q \times 2Cm  \text{(along OD)}$ $p_2 = q \times 2Cm  \text{(along OD)}$		
$p_{net} = \sqrt{p_1^2 + p_2^2}$	1/2	
$=2\sqrt{2} q Cm$		
Electric field at centre O		
$E = \frac{kp_{net}}{(r^2 + a^2)^{3/2}}$	1/2	
at point $Q$ , $r = 0$ , $a = 1$ m	72	
$E = \frac{k \times 2\sqrt{2}q}{1^3} = 2\sqrt{2}kq = \frac{2\sqrt{2}q}{4\pi \in \mathbb{R}}$	1/2	
Along DC		
and a second	1/2	

## Alternatively



$$E = \frac{kq}{r^2}$$

AC = BD = 2m

$$r = OA = OB = OC = OD = 1m$$

Electric field at O due to charges at B and D

$$E_1 = E_B + E_D$$

$$E_1 = \frac{kq}{1^2} + \frac{kq}{1^2}$$
 along OB  
= 2kq

Electric field at O due to charges at A and C

$$E_2 = E_A + E_C$$

$$E_2 = \frac{kq}{1^2} + \frac{kq}{1^2}$$

$$= 2kq \qquad \text{along OC}$$


$$E_{\text{net}} = \sqrt{E_1^2 + E_2^2}$$

$$E_{\text{net}} = \sqrt{E_1^2 + E_2^2}$$

$$= 2\sqrt{2} \text{ kq} = \frac{2\sqrt{2}q}{4\pi \in_{o}}$$

Along DC

### Alternatively



 $\frac{1}{2}$ 

 $\frac{1}{2}$ 

 $\frac{1}{2}$ 

 $\frac{1}{2}$ 

 $\frac{1}{2}$ 

Considering AB as dipole, electric field at O

$$E_1 = \frac{2kq \times a}{\left(\left(\frac{1}{\sqrt{2}}\right)^2 + \left(\frac{1}{\sqrt{2}}\right)^2\right)^{3/2}} = \frac{2kqa}{\left(\frac{1}{2} + \frac{1}{2}\right)^{3/2}} = 2kqa$$

Similarly considering DC as another dipole, electric field at O

	$\frac{(2kq \times a)}{(1+(\frac{1}{\sqrt{2}})^2)^{3/2}} = \frac{2kqa}{(\frac{1}{2}+\frac{1}{2})^{3/2}} = 2kqa$ $= 4kqa = \frac{1}{4\pi \in {}_{o}} \times 4 \times \frac{1}{\sqrt{2}} \times q$ $= 2\sqrt{2}kq = \frac{2\sqrt{2}q}{4\pi \in {}_{o}}$	1/2 1/2 1/2	5
Expression Diagram ii) Finding cu (i) The magnetic proportional to proportional to $ \overrightarrow{dB} = \frac{\mu_o}{4\pi} I \frac{\overrightarrow{dl}}{r^3} \\  dB  = \frac{\mu_o}{4\pi} \frac{Idl}{r} $	of Biot-Savart's law  In for magnetic field  2 for magnetic field lines  In for magnetic field lines  In for magnetic field 2  In for magnetic field 1  In for magnetic fi	1	
	Biot Savart's law	1/2	
According to I $\left  \overrightarrow{dB} \right  = \frac{\mu_o}{4\pi} \frac{Idl  s}{r}$ At point A	Biot-Savart's law $ \frac{\sin \theta}{c^2} $ $ \vec{l} \ \vec{dl} \ \perp \vec{a} $	1/2	

	1	
$\therefore \theta = 90^{\circ}, \sin 90^{\circ} = 1$		
Hence dB= $\frac{\mu_o}{4\pi} \frac{Idl}{a^2}$		
Magnetic field at centre		
$B = \int_{0}^{2\pi a} dB = \int_{0}^{2\pi a} \frac{\mu_o}{4\pi} \frac{Idl}{a^2}$	1/2	
$\int_{0}^{B-1} \int_{0}^{aB-1} \frac{dB}{4\pi} \frac{1}{a^2}$		
$B = \frac{\mu_o}{4\pi} \times \frac{I}{a^2} \times 2\pi a$		
$4\pi a^2 \lambda^2 \lambda^2 \lambda^2 \lambda^2 \lambda^2 \lambda^2 \lambda^2 \lambda^2 \lambda^2 \lambda$	1/2	
$B = \frac{\mu_o I}{2a}$		
Note: Give full credit of 2 marks if a student derives the expression for		
magnetic field at the axis of the loop and then puts the distance of point as 0		
from the centre.		
	1/2	
	, ,	
ii) $q=e$ , $v=10^7 \text{ms}^{-1}$ , $r=10^{-10} \text{m}$		
$i=rac{q}{T}$		
	1/2	
$=rac{ m qv}{2\pi r}$		
$=\frac{ev}{e}$		
$2\pi r$	1/2	
$= \frac{1.6 \times 10^{-19} \times 10^7}{2 \times \pi \times 10^{-10}}$	72	
$2 \times \pi \times 10^{-10}$		
$-0.8_{-10^{-2}}$		
$= \frac{0.8}{\pi} \times 10^{-2} A$	1/2	
$= 0.255 \times 10^{-2} A = 2.55 \text{ mA}$		
OR		
b) i) Derivation of expression for force 2		
Statement of Rule		
Conditions for maximum and minimum force $\frac{1}{2} + \frac{1}{2}$		
ii) Calculation of magnitude of force 1 ½		
Consider a rod of uniform cross sectional area A and length <i>l</i> . Let the		
number density of mobile charge carriers in it be n.		
Thus the total number of mobile charge carriers in it is n $l$ A. For steady current I, drift velocity of electrons $\overrightarrow{v_d}$ , in the presence of	1/2	
To steady current i, drift velocity of electrons $v_d$ , in the presence of		

<u> </u>	ı	
external magnetic field $\vec{B}$ , the force on these carriers is $\vec{F} = n l \text{Aq}(\vec{v_d} \times \vec{B})$	1/2	
$= \left[ \vec{j}Al \right] \times \vec{B}$	1/2	
$=I(\vec{l}\times\vec{B})$	1/2	
Where $nq\overrightarrow{v_d}$ is current density $(\overrightarrow{j})$ and $ \overrightarrow{j}A $ is current (I)	, 2	
Fleming's left hand Rule: If forefinger, middle finger and thumb are stretched in mutually perpendicular directions, such that forefinger indicates the direction of magnetic field, middle finger indicates the direction of current in the conductor, then thumb indicates the direction of force on the conductor.  Alternatively		
Right Hand Thumb Rule: If the fingers of right hand are made to rotate from $\vec{l}$ to $\vec{B}$ through angle $\theta$ , the thumb points in the direction of force on the current carrying conductor.  Condition for maximum force $\theta = 90^{\circ}$	1/2	
$ \vec{F}  = I l B \sin \theta = I l B$	1/2	
Condition for minimum force $\theta = 0^{\circ}$ or $180^{\circ}$ $ \vec{F}  = 0$	1/2	
ii)  5 A  A  2.5A  40cm		
$F = \frac{\mu_o}{4\pi} \frac{2I_1I_2}{d} l$ $= \frac{10^{-7} \times 2 \times 5 \times 2.5}{2.5 \times 10^{-2}} \times 10 \times 10^{-2} N$	1/2	
$= \frac{2.5 \times 10^{-2}}{2.5 \times 10^{-2}} \times 10 \times 10^{-1} \text{ N}$ $= 10^{-5} \text{ N}$	1/2	
101N	1/2	5

i) (1) Difference between interference pattern and 1+1	
diffraction pattern (2) Two factors affecting fringe width in young's double $\frac{1}{2} + \frac{1}{2}$	
slit experiment	
ii) (1) calculation of angular separation 1	
(2) calculation of distance between two maxima 1	
(1)	
(i) (1) (a) The interference pattern has a number of equally spaced bright and dark bands while diffraction pattern has a central bright maximum which is twice	
b) Interference pattern is obtained by superposing two waves originating	
From two narrow slits, while diffraction pattern is a superposition of a	
continuous family of waves originating from each point on a single slit.	
(c) The maxima in interference pattern is obtained at angle $\lambda/a$ , while the	
First minima is obtained at same angle $\lambda / a$ for diffraction pattern. (d) In interference pattern the intensity of bright fringes remain same while	1+1
n diffraction the intensity falls as we go to successive maxima away from	1.1
he center on either side.	
(any two)	
(2) Factors affecting fringes width	
Wave length ( $\lambda$ ) / distance of screen from slits (D) / separation between slits (d).	1/2 + 1/2
(any two)	1/2
(ii) (1) $ d \sin \theta = n \lambda $ $ n=1 $	/2
$\sin \theta = \frac{\lambda}{d}$	
For small angle $\sin \theta \approx \theta = \frac{\lambda}{100\lambda} = \frac{1}{100}$ radian.	1/2
$\lambda D$ and	1/
$(2) \beta = \frac{\lambda D}{d} = \theta D$	1/2
$=\frac{1}{100} \times 50 \times 10^{-2}$	
$=50 \times 10^{-4} m$	1./
= 5 mm	1/2
OR (b)	
i) Derivation of relation between u and v 3	
ii) Finding apparent position 2	

$n_i$ $i$ $N$ $R$ $v$	1	
Assume that the aperture of the surface is small as compared to other distance involved, so that small angle approximation can be made. For small angles for $\triangle NOC$ , i is the exterior angle $\therefore i = \angle NOM + \angle NCM$ $i = \frac{MN}{OM} + \frac{MN}{MC}$ Similarly $r = \angle NCM - \angle NIM$ $= \frac{MN}{MC} - \frac{MN}{MI}$ (ii) By Snell's law	1/2	
$n_1 \sin i = n_2 \sin r$ for small angles $n_1 i = n_2 r$	1/2	
substituting i and r from (i) and (ii) we get $ \frac{n_1}{OM} + \frac{n_2}{MI} = \frac{n_2 - n_1}{MC} $ Applying Cartesian coordinates $ OM = -u, MI = + v, MC = +R $ $ \frac{n_2}{v} - \frac{n_1}{u} = \frac{n_2 - n_1}{R} $	1/2	
(ii) $\frac{n_2}{v} - \frac{n_1}{u} = \frac{n_2 - n_1}{R}$ R= -6 cm, u = -3 cm, n <sub>1</sub> =1.5 n <sub>2</sub> = 1 $\frac{1}{v} + \frac{1.5}{3} = \frac{1 - 1.5}{-6}$ $\frac{1}{v} = \frac{0.5}{6} - \frac{1.5}{3}$ $\frac{1}{v} = \frac{0.5 - 3}{6}$	1½ ½ 1½	
$\frac{v}{v} = \frac{6}{1}$ $\frac{1}{v} = \frac{-2.5}{6}$ $v = -2.4 \text{ cm}$ from the left surface inside the sphere	1/2	5

	SECTION -E		
34.	a) Points at same potential b) Current through arm bg c) Potential difference across R <sub>3</sub> OR c) Power dissipated in R <sub>2</sub> 2		
	a) Points (a, b, c) (d, e) (j, f, g, h) are at same potential	1	
	Note: Give full credit if a student mentions any two points at same potential from the above. b)		
	$E = 6.0 \text{ V}$ $r = 1.0 \Omega$ $h$ $g$ $c$ $R_1 = 10 \Omega$ $R_3 = 5.0 \Omega$		
	According to Kirchhoff's loop rule for closed loop abgha $-6 + 10 I_2 + I_1 = 0$ $I_1 + 10 I_2 = 6$ (i) for closed loop acfha		
	$\begin{array}{l} -6+10 \ (I_{1}-I_{2}\ )+I_{1}\ =0 \\ 11\ I_{1}-10\ I_{2}\ =6 \end{array} \qquad (ii) \\ Adding \ (i)\ and \ (ii) \\ 12\ I_{1}\ =12 \\ I_{1}\ =1\ A \end{array}$	1/2	
	$I_2 = 0.5 \text{ A}$ = current through arm bg Note: Award 1 mark if a student calculates the current by any other method.	1/2	
	c) $V_{R3} = (I_1-I_2) \times R_3$ = 0.5 × 5 = 2.5 V	1	
	OR (c) $P = (I_1-I_2)^2 \times R_2 = (0.5)^2 \times 5$ = 1.25 W	1 1	4

35.			
	a) Tracing of path of ray		
	b) Finding velocity of light		
	OR		
	c) Definition of TIR		
	Mentioning two conditions of TIR $\frac{1}{2} + \frac{1}{2}$		
	a)		
	From fig. angle of incidence on second face $\angle i = 60^{\circ}$ critical angle $\angle i_c = 24.5^{\circ}$ $(\angle i) > (\angle i_c)$ $\therefore$ TIR takes place	1	
	b) $n = \frac{c}{v}$		
	V 2 108		
	$v = \frac{c}{n} = \frac{3 \times 10^8}{2.41} = 1.24 \times 10^8 \text{m/s}$	1	
	c) Optical Fibre / Brilliance of diamond / mirage (any two) Note: Give full credit if students mention the names of applications only.	1+1	
	OR		
	OK .		

c) When light travels from optically denser medium to rarer medium at an interface and gets reflected back into the same medium the phenomenon is called as total internal reflection.

Conditions for TIR

- 1. Light must travel from optically denser medium to rarer medium.
- 2. Angle of incidence at the interface must be greater than the critical angle for the pair of media.

 $\frac{1}{2} + \frac{1}{2}$ 

1

4